# Lite Ramps Technical specifications



#### Material

Panel : Graphite fibre/Glass fibre

Joint : Nylon
Handle : Nylon
Corner protector : Rubber
Walk surface : Rubber

Walk surface : Rubber tip paint Paint : Urethane

Colour

Walk surface : Grey
Center Line : Blue
Side Portion : Yellow
Rear : Grey
Velcro tape : Yellow

Durability

Max load : 300 kg

**Accessory** : Stepless wheelchair carrying

bag for 70 cm ramp

#### Marking

The product is manufactured in compliance with the Council Directive 93/42/EEC of June 14th 1993, including amendments, as medical device class 1.

### 700mm Lite ramp

700 mm Length Width, inner 730 mm outer 730 mm folded 365 mm Height of edge none Thickness (Fold) 38 mm Max height difference 140 mm (1:5) Weight 3,5 kg

### 850mm Lite ramp

Length : 850 mm

Width, inner : 780 mm (390 x 2)

outer : 780 mm
folded : 390 mm
Height of edge : none
Thickness (Fold) : 38 mm
Max height difference : 170 mm (1:5)

Weight : 4 kg

#### 1250mm Lite ramp

 Length
 : 1250 mm

 Width, inner outer folded
 : 760 mm

 folded
 : 390 mm

 Height of edge
 : 25 mm

 Thickness (Fold)
 : 106 mm

 Max height difference
 : 250 mm (1:5)

Weight : 6 kg

### 1650mm Lite ramp

Length : 1650 mm Width, 760 mm inner outer 780 mm folded 390 mm Height of edge 25 mm Thickness (Fold) 106 mm Max height difference 330 mm (1:5) Weight : 7,5 kg

## 2050mm Lite ramp

2050 mm Length Width, 760 mm inner outer 780 mm folded 390 mm Height of edge 25 mm Thickness (Fold) 106 mm Max height difference : 410 mm (1:5) Weight : 9,5 kg

